



# Tractor Mounted Trenchers

For Tractors from 25 to 50 HP



# LEWIS Tractor Mounted Trenchers



## Options

- Auger side discharge
- Conveyor system
- 36" chain length
- Reel assembly for pipe laying

## Auger model only


- Variable chain width
- 48" chain length

## Key Features


- Category 1, 3-point mounting for 25–50 PTO hydrostatic tractors (Non hydro tractors with a slow creep speed of up to 0.2km/h at PTO rpm are also suitable)
- PTO shaft driven with heavy duty slip clutch for overload protection
- Heavy duty gearbox and chain drive system
- Twin slatted conveyor belts
- Hydraulic drive motors
- Covered by one year warranty



# Specifications



Trencher



Conveyor unit



Variant	36" with Auger	48" with Auger	36" with Conveyor
<b>A</b> Trench Depth (mm)	915 (36")	1219 (48")	810 (32")
<b>B</b> Trench Width (mm)	152 (6") – 304 (12")		152 (6")
<b>C</b> Trench Chain Angle (deg)	65		
Weight (kgs)	385	405	695
Chain Spec	Double Standard, Anti-Back Flex 15,420kgs		
Chain Pitch (mm)	42 (2")		

**Note:** Front counter weight or loader may be necessary for proper transportation and operation of the tractor trencher. A minimum of 27HP for the tractor is recommended for use with the conveyor system