



# Snow/Dozer Blades

Front Mounted Blades

Rear Mounted Blades



## Front Mounted Blades



Universal mounting to front weight frame

Variant	1.4 m	1.6 m	1.8 m
Blade Width (mm)	1400	1600	1800
Blade Height (mm)	580	580	580
Weight (kgs)	120	150	180
Max Angle (degrees)	30	30	30
Width Fully Angled (mm)	1220	1400	1570

### Key Features

- Useful for all year round scraping, grading, dozing or snow plough duties
- Manual angling as standard
- Spring loaded glide-over mechanism for better performance on uneven ground
- Hydraulic lifting as standard
- Height-adjustable skids to prevent damage

### Options

- Universal weight frame fitting
- LEWIS Loader fitting
- Hydraulic angling
- Rubber wearstrips
- Wide range of colours available



Mounting to LEWIS Loader

## Rear Mounted Blades



Blade set in pushing mode

Variant	1.4 m	1.6 m	1.8 m
Blade Width (mm)	1400	1600	1800
Blade Height (mm)	350	350	350
Weight (kgs)	125	155	195
Max Angle (degrees)	20	20	20
Width Fully Angled (mm)	1320	1510	1700

### Key Features

- Standard category 1 3-point linkage mounted
- Peg and socket manual angling as standard
- Height-adjustable skids to prevent damage

### Options

- Hydraulic angling
- Rubber wearstrips
- Wide range of colours available



Blade set in pulling mode